

Domo Backing Rod

V 2018/07

Expansion Joint Back-up rod

Description

Domo Backing Rod is circular back-up material made from extruded polyethylene foam.



Applications

- Used as expansion joint and filler for concrete floors as well as precast, glass and metal cladding walls
- Used as a filler for decoration purposes and upholstery applications

Size & Packaging

Dimension	Standard Package
6 mm	800 m / Bag (8 pcs x 100 m)
10 mm	800 m / Bag (8 pcs x 100 m)
15 mm	360 m / Bag (6 pcs x 60 m)
20 mm	200 m / Bag (4 pcs x 50 m)
25 mm	100 m / Bag (4pcs x 25 m)
30 mm	100 m / Bag (4pcs x 25 m)
40 mm	4 m piece
50 mm	4 m piece

IMPORTERS/ DISTRIBUTORS:

Technical Characteristics

Property	Value	Test Method
Density	0.04 G/CM ³	ASTM D – 792
Cell Size	0.82 MM	ASTM D – 3576
Water Absorption	0.08 MG/CM ²	ASTM D – 570
Moisture Permeability	0.5 G/CM ² .24hr	ASTM D – 570
Elongation at Break	60%	ASTM D – 638
Thermal Conductivity	0.0406 W/M.°C	ASTM D – 5930

Storage

The product should be kept under cover, at temperatures between +0 °C and +45 °C. The product has no expiry date.

IMPORTERS/ DISTRIBUTORS: