

TECHNICAL DATASHEET

THERMOMASTER PVC

Product:	Thermomaster PVC corner bead with 8+12cm, 10+10cm, 10+15cm fiberglass mesh	
Supplier:	MASTERPLAST Kft., 8143 Sárszentmihály, Árpád u. 1/a. (www.masterplastgroup.com)	
Size, packaging:	2,5 m x 50 pcs= 125m/bundle	
Application: For the strengthening of corners of external thermal insulation sysem Embedded in the base coat, it improves the protection and mechanic resistance of the corners and makes unnecessary the overfolding of t		
Material:	Extruded and perforated PVC corner with bonded fiberglass mesh	



Properties	Relevant standards	Technical data
Thickness of PVC profile	MDV	~1,1mm
Width of PVC profile	MDV	21mm x 21mm
Length of PVC profile	MDV	250 cm
Width of fiberglass mesh	MDV	8+12cm, 10+10cm, 10+15cm (±0,5cm)
Length of fiberglass mesh	MDV	257 cm
Weight of fiberglass mesh	MDV	125 g/m²
Bonding strength of fiberglass mesh	MDV	30-50N

Storage and handling

Under dry conditions, protected against atmospheric exposure, especially sun-radiation and other heat sources as well as against rain.

Guarantee warranty

In accordance with the current legislations and the conditions of the distributor. The observation of the application rules of the product and presentation of the invoice constitute a prerequisite for possible future warranty claims.

Standards, specifications

ETAG 004, Application guidance of Thermomaster A-02 ETICS (Masterplast Group Zrt.)

Health and safety

No labelling required in accordance with the relevant regulation (EC) No. 1907/2006 of the European Parliament and of the Council (REACH).

This datasheet corresponds the current knowledge on the subject, but may be revised as new knowledge and/or experience becomes available. The product possesses the given technical characteristics. Since all variations of end-using of the product can not be anticipated, the designer/end-user's responsibility to make sure of the suitability of this underlay for particular purposes, structures.

*This technical datasheet is applied to products sold by Masterplast Kft., after 01st January 2011. and valid until withdrawal or until modification. Since this datasheet may be subject to revision, it is the responsibility of designer/end-user to make sure of possessing the latest version of the datasheet (*see date of issuing). Most recent version of this datasheet can be also accessed under www.masterplastgroup.com.

*Issued: 2011. 01. 01.