

| | | |
|------------------|---|---|
| Product: | THERMOMASTER SK 1,5 mm THERMOMASTER SK 2,0 mm Silicone, smooth render with a granules size of 1,5 / 2mm. |  |
| Supplier: | MASTERPLAST Kft., 8143 Sárszentmihály, Árpád u. 1/a. (www.masterplastgroup.com) | |
| Size, packaging: | 25 kg/plastic pail. Available in the colours of THERMOMASTER colour chart. | |
| Application: | As a top coat of THERMOMASTER EPS and ROCK thermal insulation systems, it contributes to the protection of the system against weathering and provide a decorative finish. It is also applicable as a finishing layer of properly dried (at least 2-month-old) cement plaster inside and outside of the buildings, above the level of footing. Used together with its primer in identical colour, it provides perfect covering on the whole surface. | |
| Material: | Ready to use decorative coating based on a mixture of synthetic silicone-based resin, aggregates, pigments and water. | |

| Properties | Relevant standards | Technical data |
|---|-------------------------------|--|
| Density of fresh plaster | Manufacturer's declared value | ~1,85 g/cm ³ |
| Coverage (granule size of 1,5mm) | Manufacturer's declared value | ~ 2,5 kg/m ² |
| Coverage (granule size of 2mm) | Manufacturer's declared value | ~ 3,1 kg/m ² |
| Thermal conductivity ($\lambda_{10 \text{ dry}}$) | EN 1745 | ~ 0,83 W/m.K |
| Surface drying time (20°C, rH: 65 %) | MSZ ISO 1517:1993 | ~ 6 hours |
| Drying time (total render thickness) | MSZ ISO 9117:1993 | 24 - 48 hours (max. 80 % relative humidity) |
| Adhesion on concrete | EN 1542 | 0,4 MPa (requirement: min. 0,3N/mm ²) |
| Water absorption | EN 1062-3 | W ₃ - low (requirement $\leq 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$) |
| Water vapour permeability | | |
| Classification | EN ISO 7783-2 | V ₂ (medium) |
| Water vapour transmission rate | EN ISO 7783-2 | 15 g/m ² .day < V ₂ \leq 150 g/m ² .day |
| Water vapour resistance factor (μ) | EN ISO 7783-2 | < 200 |
| Sd (water vapour diffusion-equivalent air-layer thick.) | EN ISO 7783-2 | d = 1,5mm: 0,27 m (0,14 m \leq V ₂ < 1,4 m) |
| Sd (water vapour diffusion-equivalent air-layer thick.) | EN ISO 7783-2 | d = 2,0mm: 0,36 m (0,14 m \leq V ₂ < 1,4 m) |

Storage and handling

Under dry conditions, protected against atmospheric exposure, especially sun-radiation and other heat sources. Storing temperature is between (+)5°C and (+)25°C, in closed plastic pail. In case of the prescribed storage and handling conditions, the expiry date of the product is 12 months after production. The effectiveness of the algicid is always depend on the local ambient, climatic circumstances, hence its lasting is not predictable exactly!

Guarantee, warranty

In accordance with the current legislations and the conditions of the distributor. The observation of the application rules of the product and presentation of the invoice constitute a prerequisite for possible future warranty claims. More information regarding the application and restriction of the product can be found on the productlabel at the plastic pail.

Standards, specifications

EN 15824, Application guidance of Thermomaster A-02 ETICS (Masterplast Group Zrt.)

This datasheet corresponds to our current knowledge, experiences and general informations on the subject, but may be revised as new knowledge and/or experience becomes available. It does not imply any legally binding assurance. The product possesses the given technical characteristics. Since all variations of end-using of the product can not be anticipated, the designer/end-user's responsibility to make sure of the suitability of this product for particular purposes, structures.

This technical datasheet is applied to products sold by Masterplast Kft. and valid until withdrawal or until modification. Since this datasheet may be subject to revision, it is the responsibility of designer/end-user to make sure of possessing the latest version of the datasheet (*see date of issuing). Most recent version of this datasheet can be also accessed under www.masterplastgroup.com. Modification of the technical datasheet repeals the previously issued versions!