

APV1324

FLOOR DRAIN 105×105/50 SIDE OUTLET, STAINLESS STEEL GRID, STAINLESS STEEL FLANGE AND 2ND-LEVEL-COLLAR INSULATION, COMBINED ODOUR TRAP SMART

Application:

- For the interior, where it is not expected to regularly use the drain (laundry, boiler rooms, cellars)
- For drainage of floor level
- For wheelchair access

Features:

- Stainless steel grid 102×102×5 mm
- Height adjustable neck 25 – 95 mm
- Wide insulating collar for connection to waterproofing construction
- 2nd-level-collar insulation for connecting waterproofing layer beneath the pavement
- Stainless steel collar for firm attachment of waterproofing membrane or waterproofing construction fabric
- Side connection to waste Ø50 mm
- Completely cleanable trap up to the waste pipe
- Combined odour trap
- Water column and mechanical flap effectively prevent odours from the sewer
- Compatibility with floor drain panels including wet, dry and combined odour traps SMART
- Material: polypropylene resistant to mechanical, chemical and thermal damage

Standards:

CSN EN 1253

Technical parameters:

The flow of the inlet grid	37 l/min.
Odour trap	30 mm
Load class – K3	300 kg

Scope of supply:

- Drain body Ø50 mm, side outlet
- Drain throat 105×105 mm
- Stainless steel grid
- Combined odour trap SMART
- Stainless steel flange + assembly set
- 2nd-level-collar of insulation inner Ø105 mm
- Seal Kit

Logistic information:

Weight (piece)	1.1652 kg
Dimensions (piece)	355×235×135 mm
Quantity (packing)	8 pcs
Quantity (pallet)	128 pcs

Order number:

Code	EAN
APV1324	8595580518479

