



Kimitech 120

ST8-0720

Veil fiber-glass reinforcement fabric coupled with fiberglass mesh to reinforce waterproofing and protection cycles

DESCRIPTION

Kimitech 120 is a veil fiber-glass reinforcement fabric coupled with a fiberglass mesh.

It has excellent resistance to degradation caused by alkaline environments and ageing, keeping its mechanical strength and elasticity characteristics unchanged.

USES

Kimitech 120 is used as reinforcement mesh in waterproofing cycles with Betonfix and Kimicover products:

- preliminary treatment of joints between the wall and the floor;
- waterproofing joints and fittings (in this case it is placed above the proper self-adhesive elastic strips Kimicover JOINT and Kimicover JOINT P).

APPLICATION

For the different kinds of intervention, read the specifications and the technical data sheets of the materials to be used in combination with **Kimitech 120**.

PACKAGING

Rolls:

- Width 100 cm, length 50 m

Characteriscs	Typical value
Glass fiber mesh	Glass E
Veil glass	Glass E
Glass fiber weight (g/mq)	70
Veil glass fiber weight (g/mq)	35
Total weight of fabric (g/mq)	105
Elongation at failure (%)	3,5
No wires warp (fili/10 cm)	30
No wires weft (fili/10 cm)	38
Tensile resistance load (warp) (N/5cm)	> 750
Tensile resistance load (weft) (N/5cm)	> 700
Average thickness of impregnated fabric (mm)	0,45

WARNING

Product for professional use.

The technical specifications and application methods are based on our current knowledge and experience and do not represent any form of guarantee of the final results obtainable with the product.

It is the customer's responsibility to check that this data sheet is still effective and has not been replaced with a more recent version, and that the product is suitable for the intended use.