

Polyethylene foil
0,12mm; 0,15mm

Product:	Polyethylene foil - 0,12mm; 0,15mm	
Supplier:	MASTERPLAST Kft., 8143 Sárszentmihály, Árpád u. 1/a (www.masterplastgroup.com)	
Size, packaging:	In rolls, 4m×25m=100m ²	
Application:	As a protective covering of building materials or separating layer.	
Material:	recycled Polyethylene	

Properties	Relevant standards	Technical data
Thickness	ISO 4591	0,12mm (±10%) / 0,15mm (±10%)
Length		25m (±1%)
Width	ISO 4592	4m (±1%)
Mass per unit area		105g/m ² (±10%) / 135g/m ² (±10%)
Flexibility at low temperature	EN 1109	≤ (-)20°C
Water vapour resistance factor (μ)	MSZ 10337:1989	100 000

Storage and handling
Under dry conditions, protected against atmospheric exposure, especially sun-radiation and other heat sources as well as against moisture and rain.

Guarantee, warranty
In accordance with the current legislations and the conditions of the distributor. The observation of the application rules of the product and presentation of the invoice constitute a prerequisite for possible future warranty claims.

Lehetséges veszélyek, megelőző előírások:
No labelling required in accordance with the relevant regulation (EC) No. 1907/2006 of the European Parliament and of the Council (REACH).

This datasheet corresponds the current knowledge on the subject, but may be revised as new knowledge and/or experience becomes available. The product possesses the given technical characteristics. Since all variations of end-using of the product can not be anticipated, the designer/end-user's responsibility to make sure of the suitability of this product for particular purposes, structures.

***This technical datasheet is applied to products sold by Masterplast Kft., after 01st January 2010. and valid until withdrawal or until modification.** Since this datasheet may be subject to revision, it is the responsibility of designer/end-user to make sure of possessing the latest version of the datasheet (*see date of issuing). Most recent version of this datasheet can be also accessed under www.masterplastgroup.com.

*Issued: 2010. 01. 01.