

DRY40 P

TECHNICAL DATASHEET



Product

Flexible sheet for waterproofing small dimension surfaces, to use under tiles in bathrooms, walls and floors within indoors humid areas.

Description

Flexible waterproof matting for balconies, sills and inner courtyards with an applicable area of less than 10 square metres. It is manufactured in EVAC with a width of 1.5 metres and both sides coated in polypropylene geo-textile to facilitate the optimum adherence of the cement-based adhesive used during the installation process. Furthermore, it ensures 100% water tightness as well as acting as water vapor barrier.

Features	Test Method	Unit	Tolerance	Value
Water tightness	EN 1928 Meth. B			PASS
Tensile strength	EN 12311-2 Meth. A	N/50 mm	MLV L \geq 170 MLV T \geq 120	L: 170 T: 120
Elongation	EN 12311-2 Meth. A	%	MLV L \geq 100 MLV T \geq 100	L: 100 T: 100
Reaction to fire	EN 13501-1	Euroclases		F
Length	EN 1848-2	m		5 and 30
Width	EN 1848-2	m	-0,5% and +1%	1,5
Weight	EN 1849-2	g/m ²	-5% and +10%	265
Specific weight	EN 1849-2	mm	-5% and +10%	0,48
Visible defects	EN 1850-2	mm		PASS
Straightness	EN 1848-2	mm	g \leq 50	50
Flatness	EN 1848-2	mm	p \leq 10	10

Further features	Test Method	Unit	Value
Water resistance of overlap cementitious adhesive C2	Water column	1m / 24Hrs	WATERTIGHT
Effects of chemicals	EN 1847	Values do not change after 28 days in saturated calcium hydroxide solution at 23 degrees C	

Storage

Store in original unopened packing. Protect from direct sunlight.