

ACID CLEAN TURBO

Powerful acidic cleaner

- ▷ **Removes residual adhesive, grout, lime and salts**
 - ▷ **Fast cleaning action**
 - ▷ **Without toxic fumes**
 - ▷ **Revives the colors of tiles and grouts**
-

Description

ACID CLEAN TURBO is a powerful professional acid solution suitable for the fast, effective, and in-depth cleaning of acid-resistant surfaces from cement, coatings, adhesives and grout residues. Its special composition revives the colors of tiles and grouts that had faded over time and use.

Uses

For surfaces such as:

- acid-resistant ceramic, Gres porcelain tiles, glass mosaic and Cotto
- natural and artificial stones
- concrete and cementitious coatings
- for the initial cleaning NOVACEM CREATIVE micro-pebble coatings

Suitable for cleaning from:

- cement and lime residues
- adhesives, coatings and grouts
- salts, calcium deposits and non-greasy stains
- rust and stains from pots

Suitable for indoor and outdoor applications in:

- houses
 - public areas such as restaurants, hotels, hospitals
 - industrial areas and office buildings
-

Technical Data

Product identification

Consistency	Liquid
Color	Transparent yellowish
Density	1.05 ± 0.05 kg/L
pH	0

Application procedure

Application

Depending on the type of dirt, ACID CLEAN TURBO can be diluted with water in an appropriate ratio. Subject to the type of application, spread ACID CLEAN TURBO evenly, over the area due for cleaning. Let the product act for a few to about 10 - 20minutes. If necessary, rub lightly with a sponge. At the end of the process, in all cases, carefully rinse the surface with plenty of clean water. In highly persistent or deeply soaked stains, the above procedure is repeated. When applied to polished surfaces, it is advisable to test a small, non-visible part of the surface.

Recommendations

- Do not apply:
- on acid sensitive surfaces such as polished marble
- on wood, metal and chrome-plated surfaces, anodized aluminum, stainless steel, zinc, etc.
- on materials of calcareous origin
- on the surfaces of unknown acid resistance without preparing a test area
- to remove greasy stains
- natural stones that contain iron (e.g. Serizzo), may cause discoloration

Special notes

- wait at least 7 days before using on cement-based grouts
- on concrete and cement mortars the roughness can be increased
- if dilution is required, add ACID CLEAN TURBO to the water and not vice versa
- not to be mixed with other cleaners
- when using the product, wear rubber gloves, a mask to protect the respiratory system and professional safety glasses
- before using the product, it is advisable to hermetically seal any surface that could be attacked through direct contact with the detergent or with vapors
- before using consult the safe use instructions on the label or the Safety Data Sheet
- keep out of reach of children

Consumption

Depending on the type of dirt 1L/7 - 10 m².

Storage

12 months from production date, in its sealed original packing, stored in dry conditions and temperatures between +5°C and +35°C.

Packaging

Buckets of 1 and 5 L.

Safety Instructions

For information and instructions regarding disposal and safe handling, users should refer to the latest Safety Data Sheet of the product containing ecological, toxicological and other safety related data.

Legal Notes

The technical data and recommendations contained or listed in this leaflet are the result of laboratory measurements, of our current knowledge and experience. All the above-mentioned information and specifications should in any case be considered as indicative, as they may differ from each other. The Company makes every effort to ensure the accuracy of the information provided herein. Product specifications, prices and availability are subject to change without notice and may differ from those shown.

In practice, variations in materials, substrates and on-site implementation conditions are such that no warranty can be given or implied, as to the merchantability or suitability of the materials for a particular purpose and for the exact conditions of each project. Anyone interested of using the product must be sure beforehand that the product is suitable for the intended use and in any case, the user is solely responsible for any consequences due to the use of the product. Among other things, the Company is not responsible for any normal wear or tear from environmental or other inappropriate conditions. We reserve the right to revise or change the data herein without prior notice. Restrictions and disclaimers apply to the extent permitted by applicable law. The Company has a Technical Support Department, which is the only one responsible for providing technical advice and solutions to deal with problems. Requests to the Technical Support Department are addressed and answered, only in writing.

For the latest and a valid version of the Technical Data Sheet, the user of the material must refer to our website www.novamix.gr or directly to the QR Code of the product.



DOMOCHEMICAL S.A.
40 Papanikoli str.
Chalandri, 15232, Athens
T +30 210 68 93 953
F +30 210 68 94 571
novamix@novamix.gr