



PVC Roof Drain



Product Description

System: PVC pipe system.

Scope: Drainage pipe system can be used for road drains, agricultural, railway, airport, construction and public green. PVC has the smoothest flow surface of any piping material. The pipe will not be susceptible to blockages and will maintain a high flow capacity over the life of the pipeline.

<u>Specification:</u> A plastic sewer system costs less to operate and maintain because it has greater flow capacity per given size and fewer joints. The economic life cycle of a PVC sewer system is projected at more than 50 years.

Referenced Standards: BS1329/BS1401

Size: 50 mm – 250 mm

<u>Certificate:</u> Kitemark

IMPORTERS/ DISTRIBUTORS:



Domochemica Co. Ltd www.domochemica.com.cy


2, Propylaeon Str. Strovolos Industrial Zone P.O. Box 28928,2084 Nicosia / Cyprus Tel: +357 - 22 31 27 10 Fax: +357 - 22 42 06 51





Code:	01/20/20/0605 12/01/064/7563	Material:	PVC
Description:	ROOF DRAIN	Standard:	BS1329/BS1401
Temperature:	Max 60°C / 140°F	Working Pressure:	/
Size:	75x63MM	Certificate:	KITEMARK
Connection	Socket	Color:	Grey







SIZE	d1	D1	D2	L1	L2	H1	H2
75 x 63	63.0	75	164.9	60	45	111.6	181.7

IMPORTERS/ DISTRIBUTORS:



Domochemica Co. Ltd www.domochemica.com.cy

2, Propylaeon Str. Strovolos Industrial Zone P.O. Box 28928,2084 Nicosia / Cyprus Tel: +357 - 22 31 27 10 Fax: +357 - 22 42 06 51